

forest

In keeping with nature's symmetry

Forest, a deep undulating panel emulating natures greatest gift. The depth of panel is designed to give it a high absorption of sound resulting in a super-efficient 0.95 NRC.

Forest offers a bold linear design, with its curved surface and deep channels offering a superb diffusion quality to the design.

Different colour finishes and a spray paintable option makes these panels versatile enough to be used in any environment from schools to offices. Forest provides a pattern that lends itself to any indoor space.

- Soundtect acoustic panels offer design options that are unusual and stand out, giving designers more choice and flexibility for acoustic applications.
- The panels are easily wall mounted and can be used to create floating ceilings that absorb sound and enhance sound quality.
- Reverberation is reduced by offering Class A absorption to increase speech intelligibility in a specific area while reducing background sound noise levels.
- Soundtect panels are for indoor use only but can be used in any area that acoustic treatments are required including areas of high levels of humidity such as swimming pools

Soundtect®



iorest AZELEA RED EARTH TAN PAPRIKA CORNFIELD ASH GLADE LAGOON CHARCOAL WHITE AZURE CHALK OLIVE GROVE MOSS BARK CORAL CITRINE AMETHYST CLARET SKY

Product Specifications

TYPICAL APPLICATIONS

Wall coverings

- Composition: 100% Polyester
- Low VOC
- Colourfastness Properties
 Colourfastness to Light, AATCC16(3), Class 4.5
- BS EN ISO 354:L2003.
- Certified 100% Recyclable
- Composition: 100% polyester fibre (PET) 70% recycled

FIRE RATING

- BS1 D0
- Suitable for use in Class1 and Class 0

SIZE

• 600 x 600 x 75mm

ACOUSTIC PROPERTIES

- NRC: 0.95
- EN ISO 11654:1997

INSTALLATION

Easy installation for walls

- Draw a grid of your panel configuration.
- Screw wall brackets in place making sure to use the correct bracket for the number of panels.

We supply three types of bracket:

- Corner brackets
- Two panel brackets
- Four corner brackets

Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture. Does not contain any Red List chemicals*.



45 Great Sutton Street. London. EC1V ODE | Tel: 0203 040 2939 enquiries@soundtect.com I www.soundtect.com