



## Discover the stylish, versatile and aesthetic freestyle

The Soundtect Solar Raft is another product inspired by nature which offers super acoustic control as a stunning ceiling design.

The contemporary design which consists of 26 individual baffles per set, is suited to a range of commercial applications and ensures effective acoustic management whatever the space. Each panel is standard

1200 x 300 giving an overall coverage of 2600 – 3000mm<sup>2</sup>.

With up to 70% recycled content and finely tuned reverberation and sound control, Freestyle™ is the natural choice for acoustic designs that challenge the status quo.

Developed by London-based Soundtect®, Freestyle™ panels are built to exacting quality and use all Soundtect's pioneering acoustic know-how.

### KEY FEATURES & BENEFITS

- Elevated design potential
- Incredible versatility
- Available in 24 colours
- Create bespoke designs in specific corporate or design colours
- Suspend from the ceiling to create a superb ceiling feature with fantastic sound control properties
- Excellent sound absorption
- Finely turned reverberation thanks to Soundtect's pioneering acoustic technology
- Environmentally friendly and recyclable, Freestyle™ Acoustic Panels are ideal for projects when there is an eco-conscious consideration to be made
- Manufactured by Soundtect®
- Independently certified

# freestyle

## Colour range



## Product Specifications

### TYPICAL APPLICATIONS

Ceiling rafts  
Ceiling baffles

- Composition: 100% Polyester
- Low VOC
- Colour Fastness Properties
  - Colorfastness to Light, AATCC16(3), Class 4.5
- ISO 14006 Certified Manufacturing Facility
- Certified 100% Recyclable
- Recycled Content: Up to 70% (min. 50% post consumer recycled content)

### FIRE RATING

- EN13501, Bs1d0

### SIZE

- Set of 26 Wavy 1200 x 300 x 20mm baffles installed to create a 3m 2 ceiling raft

### DENSITY THICKNESS

- 10mm, 2kg/sqm
- 20mm, 4kg/sqm

### ACOUSTIC PROPERTIES

20MM: NRC 0.85

### INSTALLATION

Each baffle is suspended from 2 fixing points which can be adjusted to the height required.

### Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture.

Does not contain any Red List chemicals\*.