

Discover the stylish, versatile and aesthetic freestyle

Ē

BEN

FEATURES

Ъ

The soundtect gridd is a lightweight acoustic ceiling raft which offers super acoustic control as a stunning ceiling design.

The contemporary design which consists of individual baffles slotted together, is suited to a range of commercial applications and ensures effective acoustic management whatever the space. Each baffle is standard 300mm depth but width, length & spacing can be tailored to create totally bespoke rafts to fit any ceiling or space

With up to 70% recycled content and finely tuned reverberation and sound control, Freestyle™ is the natural choice for acoustic designs that challenge the status quo.

Developed by London-based Soundtect[®], Freestyle[™] panels are built to exacting quality and use all Soundtect's pioneering acoustic know-how.

- Elevated design potential
- Incredible versatility
- Available in 24 colours
- Create bespoke designs in specific corporate or design colours
- Suspend from the ceiling to create a superb ceiling feature with fantastic sound control properties
- Excellent sound absorption

- Finely turned reverberation thanks to Soundtect's pioneering acoustic technology
- Environmentally friendly and recyclable, Freestyle[™] Acoustic Panels are ideal for projects when there is an eco-concious consideration to be made
- Manufactured by Soundtect[®]
- Independently certified

Soundtect®





freestyle



Product Specifications

TYPICAL APPLICATIONS

Ceiling rafts Ceiling baffles

- Composition: 100% Polyester
- Low VOC
- Colour Fastness Properties
 Colorfastness to Light, AATCC16(3), Class 4.5
- ISO 14006 Certified Manufacturing Facility
- Certified 100% Recyclable
- Recycled Content: Up to 70% (min. 50% post consumer recycled content

FIRE RATING

• EN13501, Bs1d0

SIZE

- Standard
- 300 Mm depth baffles
- 2400mm length maximumSlotted together installed to
- create a 3m² Ceiling raft.

Other sizes available on request

DENSITY THICKNESS

- 10mm, 2kg/sqm
- 20mm, 4kg/sqm

ACOUSTIC PROPERTIES

20MM: NRC 0.85

INSTALLATION

Each raft is suspended from a number of fixing points depending on size of raft which can be adjusted to the height required.

Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture. Does not contain any Red List chemicals*.





Soundtect Ltd. 45 Great Sutton Street. London. EC1V ODE | Tel: 0845 548 0518 enquiries@soundtect.com | www.soundtect.com