



# FREESTYLE timba

## Discover the stylish, versatile and aesthetic freestyle

Soundtect's Timba wood effect Freestyle™ Panels range are architecturally inspired and can be used to create stunning, utterly modern wall and ceiling designs in a range of wood effects and finishes.

The contemporary design is suited to a range of commercial applications and ensures effective acoustic management whatever the space.

With up to 70% recycled content and finely tuned reverberation and sound control, Freestyle™ is the natural choice for bespoke designs that challenge the status quo.

Developed by London-based Soundtect®, Freestyle™ panels are built to exacting quality and use all of Soundtect's pioneering acoustic know-how.

### KEY FEATURES & BENEFITS

- Elevated design potential
- Incredible versatility
- Available in a wide range of colours
- Create bespoke designs in specific corporate or design colours
- Suspend from the ceiling to create functional room or space dividers with sound control properties
- Excellent sound absorption
- Finely tuned reverberation thanks to Soundtect's pioneering acoustic technology
- Environmentally friendly and recyclable, Freestyle™ Acoustic Panels are ideal for projects when there is an eco-conscious consideration to be made
- Manufactured by Soundtect®
- Independently certified

# timba

## Colour range



AMERICAN OAK




BIRCH




BLACK STAINED OAK



CHERRY WOOD



MAHOGANNY



OAK



RUSTIC OAK

## Product Specifications

### TYPICAL APPLICATIONS

Wall coverings  
Ceiling rafts  
Ceiling baffles  
Screens and dividers

- Composition: 100% Polyester
- Low VOC
- Colour Fastness Properties
  - Colorfastness to Light, AATCC16(3), Class 4.5
- ISO 14006 Certified Manufacturing Facility
- Certified 100% Recyclable
- Recycled Content: Up to 70% (min. 50%) post consumer recycled content

### FIRE RATING

- EN13501, Bs1d0

### SIZE

- 2440 X 1220mm X 10 or 20mm

### DENSITY THICKNESS

- 10mm, 2kg/sqm
- 20mm, 4kg/sqm

### ACOUSTIC PROPERTIES

10MM: NRC 0.35  
20MM: NRC 0.65

### INSTALLATION

Freestyle™ acoustic panels can be installed by two methods.

- Suspend from ceiling as baffles, rafts, or screens
- Wall mounted Freestyle™ coverings, use an adhesive.

### Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture.

Does not contain any Red List chemicals\*.