



3D MANUFACTURER WARRANTY

3D panels are high quality, certified products manufactured and distributed by Soundtect. Soundtect manufacturer's guarantee carries a 10 year warranty for all Soundtect products, assuring it's buyers that the product meets all properties noted in the guarantee as well as committing that all Soundtect products are free of any manufacturing defects.

Soundtect Panels are manufactured under strictly controlled manufacturing facility. Using 100% Polyester with up to 70% Recycled Content, Soundtect panels are free of chemical additive, safe, non-toxic, non-allergenic, non-irritant, and certified low VOC.

Polyester is a non-toxic material, has a neutral PH value of 7.5 and is bacterial resistant.

This guarantee does not include product discoloration - due to environmental conditions outside our control such as UV exposure and products staining due to M&E equipment such as AC or local environment conditions.

Soundtect products are not suitable for external conditions or internal extreme conditions of heat or cold, environments that may be subject to high levels of humidity and or contain aggressive elements such as acids, chlorines, etc.

This guarantee is not applicable to any defects caused by mistreatment of the panels such as abuse, normal wear and tear, dilapidation or failure to provide basic maintenance where required.

Product Name

3D - CUBISM, FOREST, PRISM, TECHNICS, TETRIS, WAVE

Intended Use

Indoor decorative wall panels.

Manufacturer

Soundtect Ltd., First Floor, 3, Albermarle Way, London EC1V 4JB

Installation Methods

1. Fix to walls with manufacturer's wall brackets.

Evaluation Standard

BS EN ISO 354:L2003
EN ISO 11654:1997

CUBISM	NRC: .70
FOREST	NRC: .95
PRISM	NRC: .90
TECHNICS	NRC: .70
TETRIS	NRC: .90
WAVE	NRC: 1.0

Notified Body

Bureau Veritas Ltd. (HK)

Specifications

- 100% Polyester
- Low VOC
- Up to 70% post consumer Recycled Material
- Certified Fully Recyclable
- Safe
- Non-Toxic
- Non-irritant, non-allergenic
- No red chemicals
- 0% Water waste during manufacturing
- 0% Gas emissions during manufacturing

Reaction to Fire B-S1,D0

Colorfastness to Light

AATCC16(3), Class 4.5

Total Lead Content in Substrate

EPA3051 (M) & EPA 3052
- Less than 50 ppm

Physical Properties

Dimension	thickness
CUBISM	610 x 610 x 50mm
FOREST	600 x 600 x 75mm
PRISM	600 x 600 x 50mm
TECHNICS	600 x 600 x 50mm
TETRIS	460 x 460 x 40mm
WAVE	600 x 600 x 75mm

	weight
CUBISM	2.5kg
FOREST	2.5kg
PRISM	2.5kg
TECHNICS	2.5kg
TETRIS	2.5kg
WAVE	2.5kg

Design

Provided by Soundtect Ltd.

Please see additional Class Install Guide for more details.