



## Exceptional levels of acoustic performance

Baffles are engineered acoustical products giving exceptional levels of acoustic performance. Ideal for noisy environments where traditional acoustic ceilings are not possible.

The Baffles and rafts are installed using our unique suspension cable system allowing for easy installation and removal.

The fins are installed via circular hooped bolts with can be attached either to a suspended frame system or to hooks directly on the ceiling. For wall applications, the panels have an internal system to create a floating finish.

### KEY FEATURES & BENEFITS

- Hang from ceilings
- Arrange and combine in various formation
- Suspend from ceilings
- Layer in varying depths to create dramatic spaces
- Using the same tried and tested recycled PET bottles as our existing range.
- Cost effective solution for large installations
- Sustainable design for environmentally conscious projects

# Soundtect®



# CLASS above

## Colour range



White



Ash



Charcoal

## Product Specifications

### TYPICAL APPLICATIONS

Wall coverings

- Composition: 100% Polyester
- Low VOC
- Colourfastness Properties
  - Colourfastness to Light, AATCC16(3), Class 4.5
- BS EN ISO 354:L2003
- Certified 100% Recyclable
- PET with over 50% Recycled content

### FIRE RATING

- BS1 D0
- Suitable for use in Class1 and Class 0

### SIZE

- 300 x 1200 x 50mm
- 600 x 600 x 50mm
- 600 x 1200 x 50mm

### ACOUSTIC PROPERTIES

- NRC 0.95
- EN ISO 11654:1997

### INSTALLATION

Easy installation for ceilings

- Install the ceiling anchor.
- Insert CLASS ring into pre-formed hole on the rear of the panel.
- Attached suspension cable and adjust depth.
- Hang panel.

### Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture.

Does not contain any Red List chemicals\*.